



Strumenti per l'Espresso

*radiofonica*

**AUTOMATIC**  
2 gr



Full optional



## AUTOMATIC

2 gr

TECHNICAL FEATURES	AUTOMATIC
Espresso coffee and cappuccino machine with thermosiphonic system	2gr
E 61 brewing groups (filter holder Ø 58 mm) with 1 <b>PURGE</b> button per group	●
Body of satined stainless steel AISI 304	●
Boiler of copper with tap for manual discharge, pipes of copper and pipe fittings of brass	●
Dual gauges for boiler and pump pressure	●
<b>Automatic</b> boiler water loading	●
Programmable portion control / Single group washing	●
Built-in RPM motor pump with <b>AIR</b> cooling / Fluid-o-Tech rotary pump	●
Waterproof silicone touchpad for each group with 16 mm diam. pushbuttons: 4 volumetric metering selections programmable from the touchpad directly, 1 programming/continuous coffee button and 1 hot water button	●
LED lights on the back panel	●
Glass tube for boiler water level	●
2 multidirectional stainless steel steam wands with manual control from the <b>joystick taps</b>	●
1 multidirectional stainless steel hot water wand with manual control from its dedicated button on the touchpad	●



OPTIONAL ON DEMAND	
Alphameric Display	●
Digit Chrono	●
Lighting cup's LED	●
White filter holders for 1 and 2 cups	●
Nut wood kit: filter holders and knobs	●
Color options and aesthetic customisation	●

**ALPHAMERIC DISPLAY**

After the switch-on it displays the functional test. It displays boiler filling also when the boiler refills.  
When the machine is in use, after the functional test the alphameric display shows always hour.

**allows to plan/program:**  
CLOCK SETUP, AUTO ON/OFF, WORKING DAYS, DELIVERY TEST CRONO, DOSE SETTING, NUMBER OF COFFEES, REGENERATION SOFTNER, SERVICE, WASHING GROUP IN PROGRESS, LANGUAGE, NAME OF COMPANY, SERVICE PHONE, CHRONO FUNCTION, ON/OFF TOUCHPAD BUTTONS LED LIGHTS IDLE, KEYBOARD TYPE, FILLING UP + COFFEE, CONTINUOUS KEY, PREINFUSION SINGLE, PROBE SENSITIVITY, FILLING UP TIME-OUT

**allows to display:**  
COUNTER LITERS, TOTAL COFFEES

TECHNICAL DATA		2 gr
Voltage/Power	220 - 240 V (1F) / 400 V (3F)	3900 W
Frequency	Hz	50 - 60
Boiler	Lt	11,5
Length	mm	720
Width	mm	505
Height	mm	520
Net weight	Kg	78