



Strumenti per l'Espresso

*etnica* Display **TT**

**AUTOMATIC**  
2 gr • 3 gr



Optional:  
lighting cup's LED,  
black matt sides and  
electronic injection autosteamer

With touchpad above the groups and joystick taps, it's the evolution of Etnica Display and so the top of the range too. Always automatic, with covered groups and display, it represents, as Etnica Display, the indivisible bond between modern and ancient, where the future is son of history and the most modern technology matches with sounds and past time.





## AUTOMATIC

2 gr • 3 gr

TECHNICAL FEATURES	AUTOMATIC	
	2gr	3gr
Espresso coffee and cappuccino machine with thermosiphonic system		
E 61 brewing groups (filter holder Ø 58 mm)	•	•
Frame of pure polished super-mirror and satined stainless steel AISI 304. Finishing of transparent methacrylate	•	•
<b>Flanged</b> boiler of copper with tap for manual discharge, pipes of copper and pipe fittings of brass	•	•
Dual gauges for boiler and pump pressure	•	•
<b>Manual and automatic</b> boiler water loading	•	•
Programmable portion control / Single group washing	•	•
Built-in RPM motor pump with <b>WATER</b> cooling / Fluid-o-Tech rotary pump	•	•
Touchpad for each group with pilot lights for activated brewing buttons:		
6 volumetric metering selections programmable from the touchpad directly and 1 programming button	•	•
1 electromechanical button for every group for brewing choice (only for 2 groups in the 3 groups version)	•	•
Indicator to inform that machine and cup heater are ON	•	•
LED lights on the back panel (with ON/OFF switch)	•	•
<b>Electric cup heater (with ON/OFF switch) with programmable working temperature</b>	•	•
Glass tube for boiler water level	•	•
2 multidirectional stainless steel steam wands with manual control from the <b>joystick taps</b>	•	•
1 multidirectional stainless steel hot water wand with manual control from its dedicated button	•	•

ALPHAMERIC DISPLAY	After the switch-on it displays the functional test and malfunction notice, boiler filling, filling timeout. It displays boiler filling also when the boiler refills. When the machine is in use, after the functional test the alphanumeric display shows always the boiler temperature and pressure, hour, date, number of the weekday.		
<b>allows to plan/program:</b>			
CLOCK SETUP: hour, date, number of the weekday	PREINF. SINGLE: pre-infusion time for single and double coffee		
AUTO ON/OFF: switching ON/OFF time of the machine	WASHING GROUP IN PROGRESS: single group washing		
WORKING DAYS: coffee shop day off	MAINTENANCE: number of coffee to the next maintenance		
DELIVERY TEST CRONO: brewing time (digit chrono)	LANGUAGE: ENGL-CEL, ENGL-FAH, ITALIANO, FRANCAIS, DEUTSCHE, ESPANOL, PORTUGUES		
CUP HEATER: cup heater working temperature	<b>allows to display:</b>	•	•
AUTOSTEAMER: autosteamer temperature	COUNTER LITERS: total used litres of water		
REGEN. SOFTNER: water litres to regenerate the softner	DOSER ALARM: flowmeter malfunction times		
CHANGE PASSWORD: new password to get access to the display functions	TOTAL COFFEES: total coffee done with the automatic touchpad from installation		
	BOILER PRESSURE: boiler pressure		

OPTIONAL ON DEMAND		
Mixed hot water outlet	•	•
External motor pump (air cooling)	•	•
Raised groups	•	•
Cappuccino maker / Milk frothing wand	•	•
<b>Electronic injection autosteamer with adjustable control of speed and of pump capacity. Wand with directing holes for an elliptical steam brewing</b>	•	•
Serial interface for external connection to the cash register	•	•
Lighting cup's LED	•	•
White filter holders for 1 and 2 cups	•	•
Nut wood kit: filter holders and knobs	•	•
<b>Color options and aesthetic customisation</b>	•	•

TECHNICAL DATA		2 gr	3 gr
Voltage/Power	120 V (1F)	2600 - 2930 W	—
	220 - 240 V (1F) / 380 - 415 V (3F)	3000 - 6650 W	4500 - 6700 W
Frequency	Hz	50 - 60	
Boiler	Lt	12	17
Length	mm	740	980
Width	mm	600	
Height	mm	560	
Net weight	Kg	65	96