

phonica

SEMIAUTOMATIC

GAS KIT 2 gr





Phonica semiautomatic 2 groups is also available with GAS Kit.

It is really useful in Countries or places with high costs of electricity or with power supply instability. The advantage is also that you can easily connect the machine to a battery by an inverter because the electricity is only for the pump, for the group's solenoid valves and for the control board. When the pressure in the boiler reaches the parameter you setted the flame of the gas kit keeps it stable in order to guarantee the same constant brewing as in Phonica semiautomatic 2 groups without gas kit.





phonica

SEMIAUTOMATIC 2 gr



Strumenti per l'Espresso

TECHNICAL FEATURES	SEMI AUTOMATIC	
Espresso coffee and cappuccino machine with thermosiphonic system	2gr	
E 61 brewing groups (filter holder Ø 58 mm)	•	
Frame of pure polished super-mirror and satined stainless steel AISI 304. Finishing of black methacrylate	•	
Flanged boiler of copper with tap for manual discharge, pipes of copper and pipe fittings of brass		
Dual gauges for boiler and pump pressure		
Manual and automatic boiler water loading		
Built-in RPM motor pump with water cooling / Fluid-o-Tech rotary pump		
1 electromechanical button for every group for brewing choice	•	
Glass tube for boiler water level		
2 multidirectional stainless steel steam wands with manual control from the tap knobs		
1 multidirectional stainless steel hot water wand with manual control from its dedicated button		



OPTIONAL ON DEMAND		
External motor pump (air cooling)		
Raised groups		
Cappuccino maker / Milk frothing wand		
White filter holders for 1 and 2 cups		
Nut wood kit: filter holders and knobs		
Color options and aesthetic customisation		



TECHNICAL DATA		2 gr
Voltage/Power	120 V (1F)	2600 - 2930 W
	220 - 240 V (1F) / 380 - 415 V (3F)	3000 - 6650 W
Frequency	Hz	50 - 60
Boiler	Lt	12
Length	mm	830
Width	mm	560
Height	mm	560
Net weight	Kg	84