

phonica

AUTOMATIC • SEMIAUTOMATIC
2 gr compact • 2 gr • 3 gr



With Digit Chrono and pre-infusion setting.

Inspired by Ray Charles' life, with its design that recalls the shape of the microphones of an unforgettable epoch, Phonica wants to be a tribute to those big and unrepeatable voices of the 20th century, that will always remain in the history of music.







phonica

AUTOMATIC·SEMIAUTOMATIC

2 gr compact • 2 gr • 3 gr



Strumenti per l'Espresso

| TECHNICAL FEATURES | AUTOMATIC | | SEMI AUTOMATIC | | TIC | |
|---|-------------|-----|-------------------|-------------|--------|-----|
| Espresso coffee and cappuccino machine with thermosiphonic system | 2gr comp | 2gr | 3gr | 2gr comp | 2gr | 3gr |
| Connectability to external display (by Orchestrale distributor technician) for pre-infusion setting and other display functions | | • | • | 0 | 0 | 0 |
| E 61 brewing groups (filter holder Ø 58 mm) | • | • | • | • | • | • |
| Frame of pure polished super-mirror and satined stainless steel AISI 304. Finishing of black methacrylate | • | • | • | • | • | • |
| Flanged (2 gr. compact excluded) boiler of copper with tap for manual discharge, pipes of copper and pipe fittings of brass | • | • | • | • | • | • |
| Dual gauges for boiler and pump pressure | | • | • | • | • | • |
| Manual and automatic boiler water loading | • | • | • | • | • | • |
| Programmable portion control / Single group washing | • | • | • | 0 | 0 | 0 |
| Built-in RPM motor pump with water cooling / Fluid-o-Tech rotary pump | • | • | • | • | • | • |
| Touchpad for each group with pilot lights for activated brewing buttons: | | | • | 0 | 0 | 0 |
| 6 volumetric metering selections programmable from the touchpad directly and 1 programming button | | | | | | |
| 1 electromechanical button for every group for brewing choice (only for 2 groups in the 3 groups version) | • | • | • | • | • | • |
| Indicator to inform that machine and cup heater are ON | • | • | • | • | • | • |
| LED lights on the back panel (with ON/OFF switch) | • | • | • | • | • | • |
| Electric cup heater (with ON/OFF switch) with programmable working temperature | • | • | • | 0 | ptiona | il |
| Digit Chrono | 0 | • | • | 0 | 0 | 0 |
| LED indicator for boiler water level (filling - level reached - timeout) | 0 | • | • | 0 | 0 | 0 |
| Glass tube for boiler water level | 0 | 0 | 0 | 0 | • | • |
| 1 multidirectional stainless steel steam wand with manual control from the tap knob | • | 0 | 0 | • | 0 | 0 |
| 2 multidirectional stainless steel steam wands with manual control from the tap knobs | 0 | • | • | 0 | • | • |
| 1 multidirectional stainless steel hot water wand with manual control from the tap knob | • | 0 | 0 | • | 0 | 0 |
| 1 multidirectional stainless steel hot water wand with manual control from its dedicated button | 0 | • | • | 0 | • | • |
| | | | | | | |

| OPTIONAL ON DEMAND | | | | | | | |
|--|----------|---|---|---|---|---|--|
| Electric cup heater (with ON/OFF switch) with programmable working temperature | standard | | • | • | • | | |
| Mixed hot water outlet | 0 | • | • | 0 | 0 | 0 | |
| External motor pump (air cooling) | • | • | • | • | • | • | |
| Raised groups | • | • | | • | • | • | |
| Cappuccino maker / Milk frothing wand | • | • | • | • | • | • | |
| GAS Kit | 0 | 0 | 0 | 0 | • | 0 | |
| Serial interface for external connection to the cash register | • | • | • | 0 | 0 | 0 | |
| White filter holders for 1 and 2 cups | • | • | • | • | • | • | |
| Nut wood kit: filter holders and knobs | • | • | • | • | • | • | |
| Color options and aesthetic customisation | • | • | • | • | • | • | |

| TECHNICAL DATA | | 2 gr compact | 2 gr | 3 gr | | | |
|----------------|-------------------------------------|---------------|---------------|---------------|--|--|--|
| Voltage/Power | 120 V (1F) | 2600 - 2930 W | 2600 - 2930 W | | | | |
| | 220 - 240 V (1F) / 380 - 415 V (3F) | 3000 - 6650 W | 3000 - 6650 W | 4500 - 6700 W | | | |
| Frequency | Hz | 50 - 60 | | | | | |
| Boiler | Lt | 7 | 12 | 17 | | | |
| Length | mm | 620 | 830 | 1060 | | | |
| Width | mm | | 560 | | | | |
| Height | mm | 560 | | | | | |
| Net weight | Kg | 78 | 84 | 100 | | | |

